

close · coupled · connected



DUS1

Düsseldorf has become one of the top telecommunications centers in Germany with the national headquarters for both Vodafone and Telefonica, as well as several other telcos. As such, the city has become a magnet for technology companies as well as advertising agencies and the financial services sector. Located at the heart of the Rhine-Ruhr metropolitan region, the nLighten data center provides essential colocation services for the connectivity and telecommunications networks supporting these businesses.



nLighten Düsseldorf.Ellerstraße 101
40721 Hilden

Location specifics.

The data center is well situated, just off the A3 motorway, 15 minutes from Düsseldorf's main train station, and 20 minutes by car from Düsseldorf International Airport. Location specifics anpassen: The data center has an area of almost 1,446 m², 3,600 kW of power, an office area and ample parking space.

Like the other nLighten facilities, the Düsseldorf location enables our customers to benefit from a well-connected, high-availability data center and capable of housing high-density cabinets. The data center comes with a wide range of on-site services and a growing ecosystem of partners, all there to optimally support our customers' IT environment.

Highlights.





3,600 kW

proposed end-state site capacity



Al-readiness: Design build of up to 50+ kW rear-door cooling



Sustainability:
Commitment to a net-zero
carbon footprint



Compliance: ISO27001 in all locations

Edge data center Düsseldorf Features.



Office hours

nlighten close · coupled · connected DATA CENTER	Location	Conveniently located for easy access by road and public transport	~
	Design	Tier III design target	▽
	Connectivity	Carrier-neutral data center with diverse fibre entry points and meet-me areas	
	Cooling	Cooling and humidity design complying with ASHRAE A1 allowable category	
	Compliance	ISO27001, and programme in place for PCI-DSS, SOC1, SOC2, ISO14001, ISO 50001, ISO22301	-
	Redundant po	wer with independent A and B feeds to each cabinet	-
	Proposed end-state site capacity		3,600 kW
	Design power usage effectiveness (PUE) all phases		1.29
	Standard density		2 – 7 kW available
		· ·	- / KIV avaitable
POWER	High density p	ositions up to 12 kW Air-cooling and oor-cooling (AI-ready)	Phase 1
POWER	High density p 50+ kW rear d	ositions up to 12 kW Air-cooling and	-
	High density p 50+ kW rear d Heat recovery	ositions up to 12 kW Air-cooling and oor-cooling (AI-ready)	Phase 1
	High density p 50+ kW rear d Heat recovery	ositions up to 12 kW Air-cooling and oor-cooling (Al-ready) residual redirected to local heating networks to a carbon-free energy footprint	Feasibility study Green certificates upon request, CFE scoring
	High density p 50+ kW rear d Heat recovery	ositions up to 12 kW Air-cooling and oor-cooling (Al-ready) residual redirected to local heating networks to a carbon-free energy footprint cess control (pin / biometrics); five lines of	Phase 1 Feasibility study Green certificates upon request, CFE scoring
POWER	High density p 50+ kW rear d Heat recovery Commitment Dual factor ac defence design	ositions up to 12 kW Air-cooling and oor-cooling (Al-ready) residual redirected to local heating networks to a carbon-free energy footprint cess control (pin / biometrics); five lines of	Feasibility study Green certificates upon request, CFE scoring commitment
	High density p 50+ kW rear d Heat recovery. Commitment Dual factor ac defence design CCTV – Full co	ositions up to 12 kW Air-cooling and oor-cooling (Al-ready) residual redirected to local heating networks to a carbon-free energy footprint cess control (pin / biometrics); five lines of n target	Feasibility study Green certificates upon request, CFE scoring commitment
JSTAINABILITY	High density p 50+ kW rear d Heat recovery. Commitment Dual factor ac defence design CCTV – Full co	ositions up to 12 kW Air-cooling and oor-cooling (Al-ready) residual redirected to local heating networks to a carbon-free energy footprint cess control (pin / biometrics); five lines of n target overage, storage in compliance with local laws	Feasibility study Green certificates upon request, CFE scoring commitment
JSTAINABILITY	High density p 50+ kW rear d Heat recovery. Commitment Dual factor ac defence design CCTV – Full co	ositions up to 12 kW Air-cooling and oor-cooling (Al-ready) residual redirected to local heating networks to a carbon-free energy footprint cess control (pin / biometrics); five lines of n target overage, storage in compliance with local laws	Feasibility study Green certificates upon request, CFE scoring commitment

On-site staffing